


PLANETARY GEARBOX GPL105



		1-STAGE	2-STAGE	3-STAGE			
Ratio i:1	Max. motor shaft-ØD			Ratio i:1	Max. motor shaft-ØD	Ratio i:1	Max. motor shaft-ØD
						49	16
		56	16				
		12.25	19	64	16		
		14	16	70	16		
		16	16	80	16		
		20	16	100	16		
		24	16	120	16		
		25	12	144	16		
		3.5	19	30	12	184	16
4	16	30.67	16	235.11	16		
5	12	38.33	12	293.89	12		
6	8	46	8	352.67	8		
7.67	6	58.78	6	450.63	6		

Standard scope of delivery Gearbox lubricated for duration of service life, dust-proof package, motor pinion, mounting screws, paper gasket and assembly instructions (adapter plate optional).

Customized versions also available for small quantities.

Rated torque continuous	Type Standard	Type R	Nm	12	60	150
Rated torque intermittent	Type Standard	Type R	Nm	25	120	300
Rated torque continuous	Type V	Type S	Nm	25	120	150
Rated torque intermittent	Type V	Type S	Nm	50	150	300
Max. efficiency at rated torque			%	90	85	80
Average backlash at no load	Type Standard	Type V	arcmin ≤	20	35	50
Average backlash at no load	Type R		arcmin ≤	10	20	30
Average backlash at no load	Type S		arcmin ≤	6	12	15
Weight without adapter plate			g	3250	4750	6250
Dimension L			mm	61.5	88.5	115.5
Dimension L1			mm	40	37.5	
Dimension A			mm	18.5	16	
Dimension B			mm	40	37.5	
Max. radial load	F _R	20 mm from shaft end	N	800		
Max. axial load	F _A		N	640		
Max. continuous rated speed at drive			min ⁻¹	3000		
Max. intermittent rated speed at drive			min ⁻¹	5000		
Temperature range			°C	-25 / +90		

Type V = heavy duty version | Type R = reduced backlash version | Type S = low backlash version

Changes reserved © GYSIN AG | 05/2015